

DESCRIPTION

PENETRON® LATEX is a ready-to-use styrene-butadiene latex, freeze-thaw stable which is widely used as improver additive of cementitious mortars, coatings, repairing mortars and floor mortars. It contains an antioxidant and an antifoam factor and is compatible with most hydraulic binders. This product is free from APEOs and ammonia.

RECOMMENDED FOR

- ▶ Admixture of mortars and coatings (plasters)
- ▶ Construction, repairs and renovations
- ▶ Repair mortars (in thin layers)
- ▶ Coatings with excellent adhesion
- ▶ Screeds with abrasion resistance
- ▶ Bonding layers of old/new mortars, coatings and concrete

ADVANTAGES

- ▶ Improves workability, wet adhesion and plasticity of fresh mortars
- ▶ Has a strongly liquefying effect and reduces the water requirement at the same mortar consistency
- ▶ Improves mechanical properties, such as flexural strength, adhesive strength, abrasion resistance and reduce the surface dusting
- ▶ Reduction of capillary phenomena
- ▶ Combined with the use of polypropylene fibers etc.
- ▶ Improves chemical properties, such as water / chemical resistance and shrink/swell behaviour
- ▶ Resistance to freeze/thaw cycles

TECHNICAL CHARACTERISTICS

Characteristics	Test Result	Test Method
<i>Composition</i>	Aqueous dispersion of styrene-butadiene copolymer	
<i>Colour</i>	Milky white	
<i>Density</i>	63 lb/ft ³ (1 Kg/Lt)	
<i>Solid content</i>	47%	ISO 3251
<i>pH value</i>	10	ISO 976
<i>Viscosity</i>	90 mPas	ISO 1652
<i>Minimum film-forming temperature</i>	32°F (0 °C)	
<i>Mean Particle Size</i>	160-165 nm	
<i>Glass transition temperature</i>	17.6 °F (-8 °C)	
<i>Surface tension</i>	45 mN/m	

All data are average values obtained under laboratory conditions. Impractical use, temperature, humidity and absorption of the substrate may influence the above given values.

DIRECTIONS FOR USE

Application: PENETRON® LATEX is thoroughly mixed with mixing water, prior to its application in the mortar, using a mixing drill and a mixing wand. Indicatively, see the table below for mixing ratios of PENETRON® LATEX with water per application (see *Mixing ratios*).

CEMENT-BASED MORTAR PLASTICISER AND BONDING ENHANCER

Mixing ratios:

Mixing ratio	Application
1:1 with water	Spatter dash cementitious mortars
1:2 – 1:3 with water	Mortars
1:4 with water	Plaster

Typical mixing ratio of PENETRON® LATEX is about 5 – 10% by cement weight.

NOTE: Contact PENETRON HELLAS S.A. for further information, regarding your project.

PACKAGING

PENETRON® LATEX is available in 11 lb (5 kg) and 44 lb (20 kg) containers, with volume tape and in 1000 kg tank.

STORAGE / SHELF LIFE

PENETRON® LATEX has shelf life of at least 12 months at 41 °F – 95 °F (5 °C – 35 °C), when stored in a dry enclosed area, away from direct solar radiation. Must not come in contact with metal unprotected from corrosion or non-ferrous metals, during storage.

SAFE HANDLING INFORMATION

Prolonged contact may be irritating to skin and eyes. If contact is made, flush areas with lots of water and seek medical advice. Protective gloves, mask and goggles should be worn. For further information please refer to Safety Data Sheet. PENETRON HELLAS S.A. has recently updated Safety Data Sheet on the safe use of PENETRON® products. Each Safety Data Sheet contains health and safety information for the protection of your employees and your customers. KEEP OUT OF REACH OF CHILDREN.

WARRANTY – DISCLAIMER

PENETRON HELLAS S.A. warrants that its products are manufactured under certified ISO Standard procedures, are of excellent quality and shall be free from material defects and contain all components in their proper proportion. Should any of the products be proven defective, the liability to PENETRON HELLAS S.A. shall be limited to replacement of the material proven to be defective, since the standard application procedures have been met and the suitability of the product for the particular application have been proven. PENETRON HELLAS S.A. makes no warranty as to merchantability of fitness for a particular purpose. User, after contacting the distributor of the product, shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith. While every care has been taken, the information provided in this product's data sheet make no part of any contract. All recommendations, technical data and test data contained in this product's data sheet are based upon the results of control laboratory tests or in actual field tests. However, PENETRON HELLAS S.A. makes no warranty of any kind, concerning this data. In any case, this data are given in good faith based in the PENETRON HELLAS S.A. experience, till the publication of this sheet. Due to variance in storage, handling and applications of the materials, PENETRON HELLAS S.A. accepts no liability for the results obtained. It is suggested that potential users try small applications to determine the suitability of each individual product for their specific requirements. The users should always refer to the most recent edition of the product's data sheet. PENETRON HELLAS S.A. may particularly differentiate its versions of the product's data sheet compared with those of PENETRON INTERNATIONAL LTD or respective PENETRON companies worldwide. These changes are due to text formatting, different application weathering and procedures or different product names and aim at the optimal consumer information.