

Printing date 11.09.2018

ENETRON

Version number 1

Revision: 11.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: EP 50 A

1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.Application of the substance / the mixture: Epoxy coating

Epoxy resin

1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: PENETRON HELLAS S.A. G.E.MH. No: 07278001000
50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE TEL.: +30 210 2448250 - FAX: + 30 210 2476803
Email: info@penetron.gr Site: www.penetron.gr
1.4 Emergency telephone number:

European Emergency Tel.: 112

## **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation EC No 1272/2008 CLP:



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2H315 Causes skin irritation.Eye Irrit. 2H319 Causes serious eye irritation.Skin Sens. 1H317 May cause an allergic skin reaction.

#### 2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation. Hazard pictograms:



Signal word: Warning

| inting date 11.09                              | 2018                 | Version number 1                             | Revision: 11.09.201            |
|--|----------------------|--|--------------------------------|
| ade name: EP 5                                 | 0 A                  |  |                                |
|  |                      |  | (Contd. of page                |
| Hazard-detern                                  | nining component     | ts of labelling:                             |                                |
| reaction produc                                | t: bisphenol-A-(ep   | ichlorhydrin) epoxy resin (number average    | molecular weight $\leq$ 700)   |
|  | (C12-14-alkyloxy)    |  | -                              |
| Hazard statem                                  | ents:                |  |                                |
| H315 Causes sl                                 | in irritation.       |  |                                |
| H319 Causes se                                 | rious eye irritatior | 1.   |                                |
| H317 May caus                                  | e an allergic skin i | reaction.                                    |                                |
| H411 Toxic to                                  | aquatic life with lo | ng lasting effects.                          |                                |
| Precautionary                                  | statements           |  |                                |
| P273   |                      | o the environment.                           |                                |
| P280   | Wear protective      | e gloves/protective clothing/eye protection/ | face protection.               |
| P302+P352                                      | IF ON SKIN: W        | Wash with plenty of water.                   |                                |
| P305+P351+P3                                   |                      | inse cautiously with water for several minu  | tes. Remove contact lenses, if |
|  | <b>L</b>             | y to do. Continue rinsing.                   |                                |
| P501   | *                    | tents/container in accordance with local/reg | gional/national/international  |
|  | regulations.         |  |                                |
| 2.3 Other haza                                 |                      |  |                                |
| Results of PBT                                 | and vPvB assess      | ment   |                                |
|  | cable                |  |                                |
| <b>PBT:</b> Not appli<br><b>vPvB:</b> Not appl |                      |  |                                |

Description: Mixture: consisting of the following components.

| Description. Whitele, consisting of the following components. |  |  |  |
|---|--|--|--|
| ngredients according Regulation (EU) 830/2015:                |  |  |  |
| CAS: 25068-38-6   | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin   |  |  |
| NLP: 500-033-5  | (number average molecular weight $\leq 700$ )                |  |  |
| Index number: 603-074-00-8                                    | Aquatic Chronic 2, H411; (1) Skin Irrit. 2, H315; Eye Irrit. |  |  |
| Reg.nr.: 01-2119456619-26-XXXX                                | 2, H319; Skin Sens. 1, H317                                  |  |  |
| CAS: 68609-97-2   | oxirane, mono[(C12-14-alkyloxy)methyl] derivs                |  |  |
| EINECS: 271-846-8   | () Skin Irrit. 2, H315; Skin Sens. 1, H317                   |  |  |
| Index number: 603-103-00-4                                    |  |  |  |

# **SECTION 4: First aid measures**

Reg.nr.: 01-2119485289-22-0000

# 4.1 Description of first aid measures

General information: Seek immediate medical advice.

## After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses and continue rinsing for several minutes

Avoid strong water jet-risk of cornea damage, consult a doctor.

50-100%

10-20%

Printing date 11.09.2018

Version number 1

Revision: 11.09.2018

Trade name: EP 50 A

(Contd. of page 2)

After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately. Seek immediate medical advice.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

## **5.3 Advice for firefighters**

## **Protective equipment:**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

#### Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes.

Avoid inhalation of dust.

Ensure adequate ventilation.

6.1.1 For non-emergency personnel Avoid contact with dripping or leaking material

6.1.2 For emergency responders

First-aid responders must wear protectice clothing, gloves, goggles and respiratory device.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

## 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

**6.4 Reference to other sections:** 

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

# 7.1 Precautions for safe handling

No special measures required.

Open and handle receptacle with care.

Prevent formation of dust.

Avoid contact with skin, eyes and clothing.

Information about fire - and explosion protection: No special measures required.

(Contd. of page 3)

## Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 11.09.2018

Version number 1

Revision: 11.09.2018

Trade name: EP 50 A

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store in cool, dry conditions in well sealed receptacles.

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store under lock and key and with access restricted to technical experts or their assistants only.

**7.3 Specific end use(s)** No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

## **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

#### 8.2 Exposure controls

## 8.2.1. Appropriate engineering controls

Take appropriate protective measures with regard to the handling of chemicals and mixtures.

## Personal protective equipment

**General protective and hygienic measures:** Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

## **Respiratory protection:**



Use suitable respiratory protective device in case of insufficient ventilation.

## **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves** 

Butyl rubber, BR - 0,7 mm

Nitrile rubber, NBR- 0,4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

GB

Printing date 11.09.2018

Version number 1

Revision: 11.09.2018

```
Trade name: EP 50 A
```

(Contd. of page 4)

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. Eye protection:



Tightly sealed goggles

**Body protection:** 



Protective work clothing

Environmental exposure controls: Prevent enter of the product into drains, surface and groundwater and soil.

| SECTION 9: Physical and chemical properties               |   |                    |  |  |  |  |
|---|---|--------------------|--|--|--|--|
| 9.1 Information on basic physical and chemical properties |   |                    |  |  |  |  |
| General Information                                       |   |                    |  |  |  |  |
| Appearance:   |   |                    |  |  |  |  |
| Form:   | Liquid  |                    |  |  |  |  |
| Colour:   | Colourless                                    |                    |  |  |  |  |
| Odour:  | Characteristic                                |                    |  |  |  |  |
| Odour threshold:  | Not determined                                |                    |  |  |  |  |
| pH value:   | Not determined                                |                    |  |  |  |  |
| Flash point:  | >100 °C                                       |                    |  |  |  |  |
|   | Not Flammable                                 |                    |  |  |  |  |
|   |   |                    |  |  |  |  |
| Flammability (solid, gas):                                | Not applicable                                |                    |  |  |  |  |
| Auto-ignition temperature:                                | 455 °C  |                    |  |  |  |  |
| Decomposition temperature:                                | Not determined                                |                    |  |  |  |  |
| Auto-ignition temperature:                                | Product is not selfigniting.                  |                    |  |  |  |  |
| Explosive properties:                                     | Product does not present an explosion hazard. |                    |  |  |  |  |
| Explosion limits:   |   |                    |  |  |  |  |
| Lower:  | Not determined                                |                    |  |  |  |  |
| Upper:  | Not determined                                |                    |  |  |  |  |
| Vapour pressure at 20 °C:                                 | 0.1 hPa                                       |                    |  |  |  |  |
| Density at 20 °C:   | 1.12 g/cm <sup>3</sup> (DIN EN ISO 2811-2)    |                    |  |  |  |  |
| Relative density  | Not determined                                |                    |  |  |  |  |
| Vapour density  | Not determined                                |                    |  |  |  |  |
| Evaporation rate  | Not determined                                |                    |  |  |  |  |
|   |   |                    |  |  |  |  |
| Solubility in / Miscibility with                          | Incolubia                                     |                    |  |  |  |  |
| water:  | Insoluble                                     | (Contd. on page 6) |  |  |  |  |

Printing date 11.09.2018

Version number 1

Revision: 11.09.2018

```
Trade name: EP 50 A
```

(Contd. of page 5)

Partition coefficient: n-octanol/water: Not determined

Viscosity: Dynamic at 20 °C: Kinematic: 9.2 Other information

975 mPas (DIN EN ISO 3219) Not determined No further relevant information available.

# **SECTION 10: Stability and reactivity**

10.1 Reactivity Stable under normal conditions
10.2 Chemical stability Material is stable under normal conditions.
Thermal decomposition / conditions to be avoided Stable at environment temperature.
10.3 Possibility of hazardous reactions
Exothermic polymerisation
Reacts with alcohols.
Reacts with amines.
Reacts with alkali (lyes).
Reacts with strong acids.
10.4 Conditions to avoid No further relevant information available.
10.5 Incompatible materials No further relevant information available.
10.6 Hazardous decomposition products Corrosive gases/vapours

#### **SECTION 11: Toxicological information**

11.1 Information on toxicological effects
Acute toxicity Based on available data, the classification criteria are not met.
LD/LC50 values relevant for classification:
25068-38-6: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < 700)</li>
Oral LD50 >5000 mg/kg (rat)
Dermal LD50 >2000 mg/kg (rabbit)

68609-97-2: oxirane, mono[(C12-14-alkyloxy)methyl] derivs
Dermal LD50 26800 mg/kg (rat)
Skin corrosion/irritation
Causes skin irritation.
Serious eye damage/irritation
Causes serious eye irritation.
Respiratory or skin sensitisation
May cause an allergic skin reaction.
Repeated dose toxicity Based on the data, the classification criteria are not fulfilled.
CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.
Reproductive toxicity Based on available data, the classification criteria are not met.
STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 11.09.2018

Version number 1

Revision: 11.09.2018

```
Trade name: EP 50 A
```

## Aspiration hazard

(Contd. of page 6)

Not classified as a risk for aspiration according to paragraphs 3.10.3.3.1.1. & Amp; 3.10.3.3.1.2 of CLP Regulation 1272/2008 / EC. The viscosity of the mixture at 40 ° C is greater than 20.5 mm2 / s.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

Aquatic toxicity:

25068-38-6: reaction product - bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < 700)

EC50/48 h 1,8 mg/l (Daphnia (Wasserfloh))

EC50/96 h 220 mg/l (Grünalge (Desmodesmus subspicatus))

LC50/96 h 2 mg/l (Leuciscus idus (Goldorfe))

68609-97-2: oxirane, mono[(C12-14-alkyloxy)methyl] derivs EC50/48 h 6.08 mg/l (Daphnia (Wasserfloh))

LC50/96 h > 5000 mg/l (Leuciscus idus (Goldorfe))

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

Ecotoxical effects:

Remark: Toxic for fish

Additional ecological information:

**General notes:** 

Also poisonous for fish and plankton in water bodies.

The product contains materials that are harmful to the environment.

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

# **SECTION 13: Disposal considerations**

# **13.1** Waste treatment methods Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

## Waste disposal key:

08 04 09 - waste adhesives and sealants containing organic solvents or other dangerous substances.

## Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

GR

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018 Trade name: EP 50 A (Contd. of page 7) **SECTION 14: Transport information** 14.1 UN-Number ADR, IMDG, IATA **UN3082** 14.2 UN proper shipping name 3082 ENVIRONMENTALLY HAZARDOUS ADR SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)) IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)), MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE. ΙΑΤΑ LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight  $\leq$  700)) 14.3 Transport hazard class(es) ADR, IMDG, IATA Class 9 Miscellaneous dangerous substances and articles. Label 9 14.4 Packing group ADR, IMDG, IATA Ш 14.5 Environmental hazards: **Environmental Hazardous** Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight < 700) Marine pollutant: Yes Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) Special marking (IATA): Symbol (fish and tree) 14.6 Special precautions for user Warning: Miscellaneous dangerous substances and articles. **Danger code (Kemler):** 90 **EMS Number:** F-A.S-F **Stowage Category** А 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. **Transport/Additional information:** ADR Limited quantities (LO) 5L **Excepted quantities (EQ)** Code: E1 Maximum net quantity per inner packaging: 30 ml

(Contd. on page 9)

Maximum net quantity per outer packaging: 1000 ml

| Printing date 11.09.2018   | Version number 1        | Revision: 11.09.201            |
|----------------------------|-------------------------|--------------------------------|
| <b>Frade name:</b> EP 50 A |                         |                                |
| Transport category         | 3                       | (Contd. of page 8              |
| IMDG                       |                         |                                |
| Limited quantities (LQ)    | 5L                      |                                |
| Excepted quantities (EQ)   | Code: E1                |                                |
|                            | Maximum net quantity pe | er inner packaging: 30 ml      |
|                            |                         | er outer packaging: 1000 ml    |
| UN "Model Regulation":     | UN 3082 ENVÎRONMÊ       | NTALLY HAZARDOUS               |
| 0                          | SUBSTANCE, LIQUID,      | N.O.S. (REACTION PRODUCT:      |
|                            |                         | LORHYDRIN) EPOXY RESIN         |
|                            | (NUMBER AVERAGE ]       | MOLECULAR WEIGHT $\leq$ 700)). |
|                            | 9, 111                  | _ ,,,,                         |

## **SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed. Seveso category E2 Hazardous to the Aquatic Environment Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Other regulations, limitations and prohibitive regulations

#### Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. **Relevant phrases** 

# H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 10)

Printing date 11.09.2018

Version number 1

Revision: 11.09.2018

```
Trade name: EP 50 A
```

(Contd. of page 9)

GB

#### **Training hints**

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

#### **Department issuing SDS:**



SUSTCHEM Engineering SA REACH & Chemical Services Department 144, 3rd Septemvriou, GR 112 51, Athens, Greece Tel.: +30 210 8252510 Fax: +30 210 8252575

E-mail: info@suschem.gr

Website: www.sustchem.gr

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2