

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: EP 55 B

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available. **Application of the substance / the mixture:**

Sealing

Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

PENETRON HELLAS S.A. G.E.MH. No: 07278001000

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803 Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:



European Emergency Tel.: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H302 Harmful if swallowed. Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

Hazard pictograms:





GHS05 GHS07

Signal word: Danger

Hazard-determining components of labelling:

Benzyl alcohol

m-phenylenebis(methylamine)

3-aminomethyl-3,5,5-trimethylcyclohexylamine

4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Hazard statements:

H302+H332 Harmful if swallowed or if inhaled.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

IF ON SKIN: Wash with plenty of water. P302+P352

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

Dispose of contents/container in accordance with local/regional/national/international P501

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture: consisting of the following components.				
Ingredients according Regulation (EU) 830/2015:				
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	Benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332	25-50%		
CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50-XXXX	m-phenylenebis(methylamine) Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-<25%		
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32-XXXX	3-aminomethyl-3,5,5-trimethylcyclohexylamine Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10-<25%		

(Contd. on page 3)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

CAS: 38294-64-3
NLP: 500-101-4
Reg.nr.: 01-2119965165-33-XXXX

Skin Corr. 1A, H314; Skin Sens. 1, H317; Aquatic Chronic 3, H412

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In all cases call a doctor.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If the product causes burning or chilling, do not remove the clothing as this may aggravate the injury if the garment sticks to the skin. If blisters are formed on the skin, they should never drop because the risk of contamination will increase.

If skin irritation continues, consult a doctor.

After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses and continue rinsing for several minutes

Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.



CO2, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

(Contd. on page 4)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

(Contd. of page 3)

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes.

Avoid inhalation of dust.

Ensure adequate ventilation.

6.1.1 For non-emergency personnel Avoid contact with dripping or leaking material

6.1.2 For emergency responders

First-aid responders must wear protectice clothing, gloves, goggles and respiratory device.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures required.

Open and handle receptacle with care.

Prevent formation of dust.

Avoid contact with skin, eyes and clothing.

Ensure good ventilation.

Prevent formation of aerosols.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store in cool, dry conditions in well sealed receptacles.

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

Further information about storage conditions:

Keep container tightly sealed.

Store under lock and key and with access restricted to technical experts or their assistants only.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

38294-64-3 4,4'-Isopropylidendiphenol, oligomeric reaction products with 1-chloro-2,3,-

epox ypropane - , reaction products with 3- aminomethy 1 - 3,5, 5, -trimethylcyclohexylamine:

(Contd. on page 5)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

(Contd. of page 4)

Dermal Longterm Systemic 0,05 mg/kg bw/day (general population) 0,14 mg/kg bw/day (worker) Inhalative Longterm Systemic 0,18 mg/m³ (general population) 0,98 mg/m³ (worker)

8.2 Exposure controls

8.2.1. Appropriate engineering controls

Take appropriate protective measures with regard to the handling of chemicals and mixtures.

Personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Respiratory protection:



Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR - 0,7 mm

Nitrile rubber, NBR- 0,4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:



Tightly sealed goggles

(Contd. on page 6)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

Body protection:

(Contd. of page 5)



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Liquid
Colour: Light yellow
Odour: Amine-like
Odour threshold: Not determined

pH value: Not determined

Flash point: >100 °C

Flammability (solid, gas): Not applicable

Auto-ignition temperature: 435 °C

Decomposition temperature: Not determined

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower: 1.3 Vol % **Upper:** 13 Vol %

Vapour pressure at 20 °C: 0.1 hPa

Density at 20 °C: 1.05 g/cm³ (DIN EN ISO 2811-2)

Relative density
Vapour density
Not determined
Evaporation rate
Not determined
Not determined

Solubility in / Miscibility with

water: Not miscible

Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic at 20 °C: 625 mPas (DIN EN ISO 3219)

Kinematic: Not determined

Solvent content:

Organic solvents: 25-50 %

VOC (EC) 36.00 %

(Contd. on page 7)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

9.2 Other information

No further relevant information available.

(Contd. of page 6)

SECTION 10: Stability and reactivity

- 10.1 Reactivity Stable under normal conditions
- **10.2 Chemical stability** Material is stable under normal conditions.

Thermal decomposition / conditions to be avoided Stable at environment temperature.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5** Incompatible materials No further relevant information available.
- 10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if swallowed or if inhaled.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	>872-2,002 mg/kg
Dermal	LD50	>4,400-11,000 mg/kg
Inhalative	LC50/4 h (vapour)	>6.68-15.5 mg/l

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h (vapour)	8.8 mg/l (rat)

CAS: 1477-55-0 m-phenylenebis(methylamine)

Oral	LD50	1,040 mg/kg (rat)
Inhalative	LC50/4 h (vapour)	2.4 mg/l (rat)

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Repeated dose toxicity Based on the data, the classification criteria are not fulfilled.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Not classified as a risk for aspiration according to paragraphs 3.10.3.3.1.1. & Amp; 3.10.3.3.1.2 of CLP Regulation 1272/2008 / EC. The viscosity of the mixture at 40 ° C is greater than 20.5 mm2 / s.

- GB

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

100-51-6 Benzyl alcohol

EC50/96 h 400 mg/l (Daphnia (Wasserfloh))

640 mg/l (Scenedesmus subspicatus (Alge))

1477-55-0 m-phenylenebis(methylamine)

EC50/48 h 15.2 mg/l (Daphnia (Wasserfloh))

EC50/72h 20.3 mg/l (Scenedesmus subspicatus (Alge))

LC50/96 h 87.6 mg/l (Oryzias latipes (Ricefish))

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

EC10 1120 mg/l (Pseudomonas putida)

EC50/48 h 23 mg/l (Daphnia (Wasserfloh))

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark: Harmful to fish

Additional ecological information:

General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

The product contains materials that are harmful to the environment.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Waste disposal key:

08 04 09 - waste adhesives and sealants containing organic solvents or other dangerous substances.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

-GB

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

(Contd. of page 8)

SECTION 14: Transport information

14.1 UN-Number

ADR, IMDG, IATA UN2735

14.2 UN proper shipping name

ADR 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-

phenylenebis(methylamine), ISOPHORONEDIAMINE)

IMDG, IATA AMINES, LIQUID, CORROSIVE, N.O.S. (m-

phenylenebis(methylamine), ISOPHORONEDIAMINE)

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class 8 Corrosive substances.

Label 8

14.4 Packing group

ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant:

14.6 Special precautions for user Warning: Corrosive substances.

Danger code (Kemler):80EMS Number:F-A,S-BSegregation groupsAlkalisStowage CategoryD

Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

Handling Code H2 Keep as cool as reasonably practicable

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Transport category 2
Tunnel restriction code E

IMDG

Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

> > (Contd. on page 10)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

(Contd. of page 9)

UN "Model Regulation": UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-

PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

Training hints

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

Department issuing SDS:



SUSTCHEM Engineering SA REACH & Chemical Services Department 144, 3rd Septemvriou, GR 112 51, Athens, Greece Tel.: +30 210 8252510 Fax: +30 210 8252575

E-mail: info@suschem.gr Website: www.sustchem.gr

(Contd. on page 11)

Printing date 11.09.2018 Version number 1 Revision: 11.09.2018

Trade name: EP 55 B

(Contd. of page 10)

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB