

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: PENECOATTM PU-L **UFI:** CK70-T02D-100P-1140

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture: Polyurethane Waterproofing coating

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

PENETRON HELLAS S.A. G.E.MH. No: 07278001000

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803 Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:



European Emergency Tel.: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

of O1 SE 5 11555 way eause respiratory inflation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

Hazard pictograms:







GHS02 GHS07 GHS08

Signal word: Danger

Hazard-determining components of labelling:

Reaction mass of ethylbenzene and m-xylene and p-xylene

1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate

3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers

4,5-dichloro-2-octyl-2H-isothiazol-3-one

maleic anhydride

3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

Addition reaction products of conjugated sunflower-oil fatty acids and tall-oil fatty acids with maleic anhydride

Hazard statements:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

vPvB: Not applicable.

(Contd. of page 2)

SECTION 3: Composition/inform	nation on ingredients	
3.2 Mixtures Description: Mixture: consisting of	the following components	
Ingredients according Regulation (EU) 2020/878:		
EC number: 905-562-9 Reg.nr.: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and m-xylene and p-	≥30-<40%
CAS: 140921-24-0 ELINCS: 411-700-4 Index number: 616-079-00-5 Reg.nr.: 01-0000015906-63-XXXX	1,6-hexanediyl-bis(2-(2-(1-ethylpentyl)-3-oxazolidinyl)ethyl)carbamate Skin Sens. 1, H317	≥3-<5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	≥3-<5%
CAS: 53880-05-0 NLP: 500-125-5 Reg.nr.: 01-2119488734-24-XXXX	3-Isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate, oligomers Skin Sens. 1B, H317; STOT SE 3, H335	≥3-<5%
CAS: 4098-71-9 EINECS: 223-861-6 Index number: 615-008-00-5	3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate Acute Tox. 3, H331; Resp. Sens. 1, H334; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	≥0.25-<0.5%
EC number: 701-043-4 Reg.nr.: 01-2119976378-19-XXXX	Addition reaction products of conjugated sunflower- oil fatty acids and tall-oil fatty acids with maleic anhydride Skin Irrit. 2, H315; Skin Sens. 1, H317	≥0.1-<1%
CAS: 64359-81-5 EINECS: 264-843-8 Index number: 613-335-00-8	4,5-dichloro-2-octyl-2H-isothiazol-3-one Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 0.025 % Eye Irrit. 2; H319: C ≥ 0.025 % Skin Sens. 1A; H317: C ≥ 0.0015 %	≥0.0025-<0.025

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

		(Contd. of page 3)
CAS: 108-31-6	maleic anhydride	≥0.001-<0.1%
EINECS: 203-571-6	♦ Resp. Sens. 1, H334; STOT RE 1, H372; ♦ Skin	
Index number: 607-096-00-9	Corr. 1B, H314; (1) Acute Tox. 4, H302; Skin Sens.	
Reg.nr.: 01-2119472428-31-XXXX	1, H317	
	Specific concentration limit:	
	Skin Sens. 1A; H317: C ≥ 0.001 %	
CAS: 13463-67-7	titanium dioxide	≥10-<20%
EINECS: 236-675-5	substance with a Community workplace exposure	
Index number: 022-006-00-2	limit	
Reg.nr.: 01-2119489379-17-XXXX		
_		

Additional information:

(CAS:13463-67-7) Titanium dioxide

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter \leq 10 μ m.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Remove contaminated clothing.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for at least 15 minutes under running water.

Protect unharmed eye.

Seek immediate medical advice.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

(Contd. on page 5)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

(Contd. of page 4)

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Wear fully protective suit.

Wear self-contained respiratory protective device.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Avoid inhalation of vapors.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Collect with absorbent material (sand, diatomite).

Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:**





Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Provide ventilation for receptacles.

Store away from sources of ignition

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

GB

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

(Contd. of page 5)

SECTION 8: Expos	ure controls/personal protection		
-	8.1 Control parameters		
Ingredients with limit values that require monitoring at the workplace:			
CAS: 13463-67-7 titanium dioxide			
WEL (Great Britain)	Long-term value: 10* 4** mg/m³ *total inhalable **respirable		
CAS: 108-65-6 2-methoxy-1-methylethyl acetate			
WEL (Great Britain)	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk		
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin		
CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate			
WEL (Great Britain)	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO		
CAS: 108-31-6 maleic anhydride			
WEL (Great Britain)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen		

DNELs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

DNEL Workers:

Inhalation - Intensive systemic effect = 289 mg / m 3 Inhalation - Chronic systemic effect = 77 mg / m 3 Skin - Chronic systemic effect = 180 mg / kg

DNEL Consumers:

Mouth - Chronic systemic effect = 1.6 mg / kg

Inhalation - Intensive systemic effect = 174 mg/m 3

Inhalation - Chronic systemic effect = 14.8 mg/m 3

Skin - Chronic systemic effect = 108 mg / kg

Titanium dioxide cas: 13463-67-7

DNEL: 10 mg/m³

PNECs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

PNEC:

in fresh water 0.327 mg/1

in marine water 0,327 mg/1

for sediment in fresh water 12,46 mg/kg

for sediment in marinewater 12,46 mg / kg

for water, intermittent release of 0.327 mg/1

for STP 6.58 mg / 1 microorganisms

for the terrestrial area of 2,31 mg/kg

(Contd. on page 7)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

(Contd. of page 6)

Ingredients with biological limit values:

CAS: 4098-71-9 3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate

BMGV (Great Britain) 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

8.2 Exposure controls

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while using the product.

Ensure adequate ventilation during use.

Be sure to clean skin thoroughly after work and before breaks.

The usual precautionary measures are to be adhered to when handling chemicals.

Respiratory protection:



Use suitable respiratory protective device in case of insufficient ventilation. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter A2-P2 (EN529) is recommended.

Hand protection



Protective gloves resistant to chemicals (standard EN 374-1)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Hand protection when handling the product at room temperature:

Butyl rubber - IIR: thickness ≥0,5mm; breakthrough time ≥480min.

Fluorinated rubber - FKM: thickness ≥0,4mm; breakthrough time ≥480min.

Recommendation: contaminated gloves should be disposed of.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection



Safety glasses with side-shields (frame goggles) (e.g. EN 166)

(Contd. on page 8)

(Contd. of page 7)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

Body protection:





Chemically resistant, protective work clothing (EN 14605) and boots.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Liquid

Colour:Various coloursOdour:CharacteristicOdour threshold:Not determinedMelting point/freezing point:Not determined

Boiling point or initial boiling point and boiling

range 130 °C

Flammability Not applicable

Lower and upper explosion limit

Lower: 0.8 Vol % Upper: Not determined

Flash point: 27-32 °C (closed cup, Reaction mass of ethylbenzene

and m-xylene and p-xylene)

Auto-ignition temperature: Product is not selfigniting.

Decomposition temperature: Proof: Not determined
Not determined

Viscosity:

Kinematic viscosity Not determined

Kinematic viscosity

Dynamic at 20 °C: >40 mPas

Solubility

water:Not misciblePartition coefficient n-octanol/water (log value)Not determinedVapour pressure:Not determined

Density and/or relative density

Density at 20 °C:1.14 g/cm³Relative densityNot determinedVapour densityNot determined

9.2 Other information

Appearance:

Form: Liquid

Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: 488 °C (xylene)

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

VOC (EC) 460 g/l

Cloud point / clarification point:

Oxidising properties Not considered as oxidising.

(Contd. on page 9)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

Evaporation rate	Not determined	(Contd. of page 8)
Information with regard to physical hazard cl	asses	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids		
Flammable liquid and vapour.		
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	ble	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Avoid heat, sparkles, naked flame or other sources of ignition.
- 10.5 Incompatible materials No further relevant information available.
- **10.6 Hazardous decomposition products** No dangerous decomposition products known.

SECTION 11: Toxicological information		
		ses as defined in Regulation (EC) No 1272/2008
Acute toxicity Based on available data, the classification criteria are not met.		
LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Dermal	LD50	2,933 mg/kg
Inhalative	LC50/4 h (vapour)	>28.2 mg/l
Reaction mass of ethylbenzene and m-xylene and p-xylene		
Oral	LD50	4,300 mg/kg (rat)
Inhalative	LC50 (4h)	5,000 ppm (rat)
		5,000 ppm (rabbit)
CAS: 108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	>5,000 mg/kg (rat)

(Contd. on page 10)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

		(Contd. of page 9)	
Dermal	LD50	>5,000 mg/kg (rat)	
Inhalative	LC50 (4h)	1,805.05 ppm (rat)	
CAS: 643:	CAS: 64359-81-5 4,5-dichloro-2-octyl-2H-isothiazol-3-one		
Oral	LD50	567 mg/kg (ATE)	
Inhalative	LC50/4h (dusts and mists)	0.16 mg/l	
CAS: 108-31-6 maleic anhydride			
Oral	LD50	400 mg/kg (rat)	
Dermal	LD50	2,620 mg/kg (rabbit)	

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3

May cause respiratory irritation.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

The product is classified Aspiration toxicity Category 1

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

EC50 (48h) 8.8 mg/l (crustacean)

LC50 (96h) 6.83 mg/l (fis)

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects Remark: Harmful to fish

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 11)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

(Contd. of page 10)

The product contains materials that are harmful to the environment.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1866

14.2 UN proper shipping name

ADR 1866 RESIN SOLUTION IMDG, IATA RESIN SOLUTION

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): 30 F-E,S-E

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

(Contd. on page 12)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

(Contd. of page 11)

Transport/Additional information:

ADR

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

Transport category 3
Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

> Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 94/62/EC on packaging and packaging waste.

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

(Contd. on page 13)

(Contd. of page 12)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. Harmful in contact with skin. H312 H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. May cause an allergic skin reaction. H317 H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. H331 Toxic if inhaled. H332 Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334 H335 May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure. H372 H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with long lasting effects. H411 H412 Harmful to aquatic life with long lasting effects. EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing SDS:



SUST SUSTCHEM S.A.

REACH & Chemical Services Department

A: 144, 3rd Septemvriou, GR 112 51 | Athens, Greece

T: +30 210 8252510 | F: +30 210 8252575 W: www.sustchem.gr | E: info@suschem.gr

Version number of previous version: 4

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

(Contd. on page 14)

(Contd. of page 13)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 21.07.2021 Version number 5 (replaces version 4) Revision: 21.07.2021

Trade name: PENECOATTM PU-L

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.