

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: PENEPRIMERTM PU UFI: U440-J0FG-S00V-KCTE

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture: Polyurethane primer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

PENETRON HELLAS S.A. G.E.MH. No: 07278001000

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803 Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:



European Emergency Tel.: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation EC No 1272/2008 CLP:



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

(Contd. of page 1)

2.2 Label elements

Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:







GHS02 GHS07 GHS08

Signal word: Danger

Hazard-determining components of labelling:

Reaction mass of ethylbenzene and m-xylene and p-xylene

diphenylmethane diisocyanate, isomeres and homologues

maleic anhydride

m-tolylidene diisocyanate

Addition reaction products of conjugated sunflower-oil fatty acids and tall-oil fatty acids with maleic anhydride

Xylene mixture of isomers

Hazard statements:

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P308+P313

P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing
	protection.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

(Contd. on page 3)

(Contd. of page 2)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

3.2 Mixtures Description: Mixture: consisting of the following components.			
Ingredients according Regulation (EU) 2020/878:			
EC number: 905-562-9 Reg.nr.: 01-2119488216-32-XXXX	Reaction mass of ethylbenzene and m-xylene and p-xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	25-50%	
CAS: 9016-87-9	diphenylmethane diisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 % Resp. Sens. 1; H334: C ≥ 0.1 % STOT SE 3; H335: C ≥ 5 %	10-25%	
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226	10-25%	
CAS: 26471-62-5 EINECS: 247-722-4 Index number: 615-006-00-4 Reg.nr.: 01-2119454791-34-XXXX	m-tolylidene diisocyanate Acute Tox. 2, H330; Resp. Sens. 1, H334; Carc. 2, H351; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335; Aquatic Chronic 3, H412, EUH204 Specific concentration limit: Resp. Sens. 1; H334: C ≥ 0.1 %	≥0.1-<19	

GB

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

		(Contd. of page 3)
EC number: 701-043-4	Addition reaction products of conjugated sunflower-oil	≥0.1-<1%
Reg.nr.: 01-2119976378-19-XXXX	fatty acids and tall-oil fatty acids with maleic anhydride	
	🕔 Skin Irrit. 2, H315; Skin Sens. 1, H317	
CAS: 108-31-6	maleic anhydride	≥0.001-<0.1%
EINECS: 203-571-6	🕸 Resp. Sens. 1, H334; STOT RE 1, H372; 📀 Skin	
Index number: 607-096-00-9	Corr. 1B, H314; Acute Tox. 4, H302; Skin Sens. 1,	
Reg.nr.: 01-2119472428-31-XXXX		
	Specific concentration limit:	
	Skin Sens. 1A; H317: C ≥ 0.001 %	
CAS: 1330-20-7	Xylene mixture of isomers	≥0.001-<0.1%
EINECS: 215-535-7	♦ Flam. Liq. 3, H226; ♦ STOT RE 2, H373; Asp. Tox.	
Index number: 601-022-00-9	1, H304; (1) Acute Tox. 4, H312; Acute Tox. 4, H332;	
Reg.nr.: 01-2119488216-32-XXXX		
	•	
	I .	

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Personal protection for the First Aider.

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment in case of complaints.

After skin contact:

Remove contaminated clothing.

Wash the skin immediately with soap and water.

Seek immediate medical advice.

After eye contact:

Rinse opened eye for at least 15 minutes under running water.

Protect unharmed eye.

Seek immediate medical advice.

After swallowing:

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray.

For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 5)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

(Contd. of page 4)

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Mouth respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from ignition sources.

Avoid inhalation of vapors.

Wear protective clothing.

Avoid contact with the skin, eyes and clothing.

6.1.1 For non-emergency personnel Ensure sufficient ventilation.

6.1.2 For emergency responders

Wear protective equipment. Keep unprotected persons away.

First-aid responders must wear protectice clothing, gloves, goggles and respiratory device with filter type A.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Collect with absorbent material (sand, diatomite).

Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:





Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep away from heat, sparks, open flames and hot surfaces.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Store away from sources of ignition

Provide ventilation for receptacles.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

-GB

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

(Contd. of page 5)

SECTION 8: Exposi	ure controls/personal protection	
8.1 Control parameters		
Ingredients with limit values that require monitoring at the workplace:		
CAS: 9016-87-9 diphenylmethane diisocyanate,isomeres and homologues		
WEL (Great Britain)	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO	
CAS: 108-65-6 2-methoxy-1-methylethyl acetate		
WEL (Great Britain)	Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk	
IOELV (EU)	Short-term value: 550 mg/m³, 100 ppm Long-term value: 275 mg/m³, 50 ppm Skin	
CAS: 26471-62-5 m-	tolylidene diisocyanate	
WEL (Great Britain)	Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO	
CAS: 108-31-6 male	ic anhydride	
WEL (Great Britain)	Short-term value: 3 mg/m³ Long-term value: 1 mg/m³ Sen	

DNELs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

DNEL Workers:

Inhalation - Intensive systemic effect = 289 mg / m 3 Inhalation - Chronic systemic effect = 77 mg / m 3 Skin - Chronic systemic effect = 180 mg / kg

DNEL Consumers:

Mouth - Chronic systemic effect = 1.6 mg / kg

Inhalation - Intensive systemic effect = 174 mg/m 3

Inhalation - Chronic systemic effect = 14.8 mg / m 3

Skin - Chronic systemic effect = 108 mg / kg

PNECs

ETHYLBENZOLE REACTION MIXTURE, m-Xylol and p-Xylol.

PNEC

in fresh water 0.327 mg / 1

in marine water 0,327 mg/1

for sediment in fresh water 12,46 mg / kg

for sediment in marinewater 12,46 mg / kg

for water, intermittent release of 0.327 mg/1

for STP 6.58 mg / 1 microorganisms

for the terrestrial area of 2,31 mg/kg

(Contd. on page 7)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

(Contd. of page 6)

8.2 Exposure controls

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not eat, drink or smoke while using the product.

Do not breathe vapours or mists.

Avoid contact with the eyes and skin.

Respiratory protection:



Use suitable respiratory protective device in case of insufficient ventilation. Respiratory protection required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter A2-P2 (EN529) is recommended.

Hand protection



Protective gloves resistant to chemicals (standard EN 374-1)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Hand protection when handling the product at room temperature:

Butyl rubber - IIR: thickness ≥0,5mm; breakthrough time ≥480min.

Fluorinated rubber - FKM: thickness ≥0,4mm; breakthrough time ≥480min.

Recommendation: contaminated gloves should be disposed of.

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection



Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:





Chemically resistant, protective work clothing (EN 14605) and boots.

CP

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

(Contd. of page 7)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Liquid

Colour: transparent/yellowish

Odour:CharacteristicOdour threshold:Not determinedMelting point/freezing point:Not determined

Boiling point or initial boiling point and boiling

range 130 °C

Flammability Not applicable

Lower and upper explosion limit

Lower: 0.8 Vol % **Upper:** 10.8 Vol %

Flash point: 27-32 °C (xylene, Reaction mass of ethylbenzene and

m-xylene and p-xylene)

Auto-ignition temperature: Product is not selfigniting.

Decomposition temperature: Not determined

Viscosity:

Kinematic viscosity Not determined

Kinematic viscosity

Dynamic at 20 °C: <40 mPas

Solubility

water:Not misciblePartition coefficient n-octanol/water (log value)Not determinedVapour pressure:Not determined

Density and/or relative density

Density at 20 °C: 1 g/cm³

Relative density Not determined Vapour density Not determined

9.2 Other information VOC(g/l): 498

Appearance:

Form: Liquid

Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: 488 °C (xylene)

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

VOC (EC) 498 g/l

Cloud point / clarification point:

Oxidising properties Not considered as oxidising.

Evaporation rate Not determined

Information with regard to physical hazard classes

ExplosivesVoidFlammable gasesVoidAerosolsVoidOxidising gasesVoid

(Contd. on page 9)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

Gases under pressure	Void	(Contd. of page 8)
Flammable liquids	VOIG	
<u>-</u>		
Flammable liquid and vapour.		
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	ble	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- 10.2 Chemical stability

Thermal decomposition / conditions to be avoided Stable at environment temperature.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid Avoid heat, sparkles, naked flame or other sources of ignition.
- **10.5** Incompatible materials No further relevant information available.
- 10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information	SECTION	11: Toxi	cological	informa	tion
--	---------	----------	-----------	---------	------

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Harmful if inhaled.

LD/LC50 values relevant for classification:

LD/LC30	LD/LC50 values relevant for classification:			
Inhalative	ATEmix (vapours)	17.7 mg/l (rat)		
Reaction 1	Reaction mass of ethylbenzene and m-xylene and p-xylene			
Oral	LD50	4,300 mg/kg (rat)		
Inhalative	LC50 (4h)	5,000 ppm (rat)		
		5,000 ppm (rabbit)		
CAS: 9010	CAS: 9016-87-9 diphenylmethane diisocyanate,isomeres and homologues			
Oral	LD50	>10,000 mg/kg (rat)		
Dermal	LD50	>10,000 mg/kg (rabbit)		
Inhalative LC50/4 h (vapour) 0.493 mg/l (rat) (OECD 401)		0.493 mg/l (rat) (OECD 401)		
	0.493 mg/l (rabbit)			
CAS: 108-	CAS: 108-65-6 2-methoxy-1-methylethyl acetate			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rat)		
Inhalative	LC50 (4h)	1,805.05 ppm (rat)		

(Contd. on page 10)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMER™ PU

	(Contd. o		
CAS: 133	CAS: 1330-20-7 Xylene mixture of isomers		
Oral	LD50	4,300 mg/kg (rat)	
Dermal	LD50	1,700 mg/kg (rabbit)	
Inhalative	LC50 (4h)	5,000 ppm (rat)	
CAS: 26471-62-5 m-tolylidene diisocyanate			
Oral	LD50	4,130 mg/kg (rat)	
Dermal	LD50	>9,400 mg/kg (rabbit)	
CAS: 108-31-6 maleic anhydride			
Oral	LD50	400 mg/kg (rat)	
Dermal	LD50	2,620 mg/kg (rabbit)	

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity

Carcinogen, Category 2

Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3

May cause respiratory irritation.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

The product is classified Aspiration toxicity Category 1

May be fatal if swallowed and enters airways.

Additional toxicological information:

Sensitisation Sensitization possible through skin contact

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

NOEC (28d) 1.659 mg/l (crustacean)

Carc. 2

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

EC50 (48h) 8.8 mg/l (crustacean)

(Contd. on page 11)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

	(Contd. of page 10)		
LC50 (96h)	6.83 mg/l (fis)		
CAS: 1330-20-7 Xylene mixture of isomers			
EC50 (48h)	>7.4 mg/l (daphnia magna)		
LC50 (96h)	2.6 mg/l (fis)		
NOEC r (72h) 440 mg/l (algae)			
CAS: 26471-62-5 m-tolylidene diisocyanate			
EC50 (48h)	12.5 mg/l (daphnia magna)		
LC50 (96h)	133 mg/l (Oncorhynchus mykiss)		

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment

PBT: Not applicable. **vPvB:** Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects Remark: Harmful to fish

Additional ecological information:

General notes:

The product contains materials that are harmful to the environment.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA UN1866

14.2 UN proper shipping name

ADR 1866 RESIN SOLUTION IMDG, IATA RESIN SOLUTION

(Contd. on page 12)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMERTM PU

14.3 Transport hazard class(es)

(Contd. of page 11)

ADR, IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR, IMDG, IATA

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Flammable liquids.

 $\begin{array}{ll} \textbf{Hazard identification number (Kemler code):} & 30 \\ \textbf{EMS Number:} & \textbf{F-E,}\underline{\textbf{S-E}} \\ \textbf{Stowage Category} & \textbf{A} \end{array}$

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category 3
Tunnel restriction code D/E

IMDG

Limited quantities (LQ) 5L Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation": UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 94/62/EC on packaging and packaging waste.

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

(Contd. on page 13)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMER™ PU

Seveso category P5c FLAMMABLE LIQUIDS

(Contd. of page 12)

Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 74

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

EUH204 Contains isocyanates. May produce an allergic reaction.

Department issuing SDS:



SUSTCHEM S.A.

REACH & Chemical Services Department

A: 144, 3rd Septemyriou, GR 112 51 | Athens, Greece

T: +30 210 8252510 | F: +30 210 8252575

W: www.sustchem.gr | E: info@suschem.gr

Version number of previous version: 4

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

(Contd. on page 14)

(Contd. of page 13)

Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 03.06.2021 Version number 5 (replaces version 4) Revision: 03.06.2021

Trade name: PENEPRIMER™ PU

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

GB